



METAL MASK

APPLICATION INFORMATION

Warning: Please read and understand these instructions thoroughly failure to do so can result in premature coating failure and/or a big mess

PRODUCT DESCRIPTION

Metal Mask is a super-tough single component polyurethane coating that makes any metal surface look exactly like new bare metal. **Metal Mask** is non-porous and will not crack, chip or peel when properly applied. It has great scratch and abrasion resistance and is not sensitive to UV light. Follow directions carefully and you will be rewarded with the finest protective coating for metal available anywhere!

Metal Mask can permanently coat and protect all of those components on your chassis that were left unpainted by the factory when your vehicle was new. Items such as spindles, steering boxes, coil brackets, rear ends, leaf springs, bolt heads, suspension components, master cylinders, coil springs, gas tanks, cast iron transmission housings, and others will look "factory correct" when coated with **Metal Mask**.

APPLICATION PROCEDURES

Use in a well ventilated area.

For best results, when applying over bare metal, smooth surfaces should be well keyed up with 300 grit sandpaper, for un-sandblasted metal, wash with **Marine Clean** to remove oils and residues, then prep your job with **POR15 Metal Ready**, Keep wet for 15-20 minutes, then wash off thoroughly with water. Ensure the surface is totally dry.

Stir contents of can well, then apply **Metal Mask** with a foam brush, rag or paint brush. Try to avoid painting back and forth. Apply in thin, covering coats, using single, steady strokes to avoid 'flooding' your job with too much paint, which could cause it to 'run' and streak. Continue to stir **Metal Mask** so that metallic pigments remain in solution as you paint.

Allow 3-4 days for **Metal Mask** to reach maximum hardness.

Moisture will shorten the life of unused **Metal Mask**. Seal can immediately after using. **Metal Mask** will withstand heat up to 148 °C.

SPRAY APPLICATION: Use 25-30lbs pressure for normal gloss. Use only **POR15 Solvent** for thinning. **Avoid skin contact. Remove from skin at once to avoid temporary staining.**

USE OF PROTECTIVE GLOVES AND VENTILATING EQUIPMENT IS RECOMMENDED.

NOTE: Organic vapour particulate respirators, NIOSH/MSHA approved must be used when spraying Metal Mask in a well-ventilated area.

When spraying in an enclosed area, air-supplied respirator must be used.

KEEP OUT OF THE REACH OF CHILDREN. HARMFUL OR FATAL IF SWALLOWED.

USE IN WELL VENTILATED AREAS ONLY.

Hazardous Ingredients: Oil Polyurethane, CAS: Proprietary Aliphatic hydrocarbon, CAS# 64741-41-9, Aluminium, CAS# 7429-90-5, Manganese Oxide, CAS# 1313-13-9, Iron Oxide, CAS# 1309-37-1, Silicon Dioxide, CAS# 7631-86-9, Aluminium Dioxide, CAS# 1344-28-1

The information set out in this flier is, so far as can be ascertained, true and accurate, but all recommendations are made without guarantee.

Since the conditions of use of the Products sold by Permanent Painted Coatings Limited (New Zealand) ("PPC Limited") and Permanent Painted Coatings Pty Ltd (Australia) ("PPC Pty Ltd") are beyond the control of PPC Ltd and/or PPC Pty Ltd ("the Companies"), then the Companies to the full extent allowed by the law, disclaim any liability with respect to damage, injury or death consequent upon the use of the Products or consequent upon the use of the information contained herein. The Companies warrant that the Products supplied hereunder shall conform to the description or specification stated in this flier. The Companies make no warranties that Products supplied are made to certain industry specifications. To the full extent allowed by law, the liability of the Companies with respect to any breach of the aforesaid warranty shall be limited, at the option of the Companies, to payment of the cost of replacing the Products or of acquiring equivalent products and in no case shall the Companies be liable for consequential loss or damage. In no case will the Companies be liable to defend or pay award of damages assessed against the buyer in any suit or cause of action alleging that the use of the Products supplied hereunder infringe any patent. The Companies hereby expressly disclaim any written or unwritten, express or implied representation, warranty or condition against infringement of any patent with respect to such goods.



Permanent Painted Coatings

PERMANENT PAINTED COATINGS (2009) LTD

P O BOX 5614, Frankton, Hamilton 3242

Email: sales@por15.co.nz

Website: www.por15.co.nz